



## 2-STROKE SYNTHETIC LUBRICANT

### Original TechniPlate®

Pure synthetic bases are blended for the perfect level of 2-stroke lubrication and performance. Klotz Clean Burn™ technology virtually eliminates carbon and residue build-up. Extreme film strength engineered to reduce engine component wear and increase horsepower. Klotz Original TechniPlate® will challenge and outrun the competition in the following ways:

- **TechniPlate® Peak Film Strength and Anti-Scuff protection**
- **Extreme Load Carrying Capacity engineered to reduce engine wear**
- **Clean Burn™ Technology reduces carbon and residue build-up**
- **Contains familiar Klotz Red for easy mixing and racy odor**



#### CHARACTERISTICS

Smoke Rating	10	Scale 1 = Fog - 10 = No Smoke
Clean Burn™	10	Scale 1 = Heavy Deposits - 10 = No Carbon
Film Strength	8	Scale 1 = Failure - 10 = No Wear
Pour Point	-15°F	
Flash Point	460°F	
Maximum RPM	13,000	
Viscosity @ 100°C	23.30 cSt Typical	
Product Color	Red	
Chemical	100% Pure Synthetic	
Biodegradable	100%	

#### CERTIFICATIONS

None

#### DIRECTIONS

**Air cooled engines:** mix at 16:1 to 20:1  
**Water cooled engines:** mix at 20:1 to 32:1  
**R/C Model:** 2-stroke glow engines mix at 15 – 18%  
**Kart:** Air-cooled mix at 16:1 to 20:1

**2-Stroke pre-mix: Do not use in oil injection systems**

#### COMPATIBILITY

Blends with BēNOL® castor oil, Super TechniPlate®, gasoline, E-85, methanol alcohol, nitromethane and stays in suspension. Will not blend with petroleum oils or synthetic lubricants.

Will blend in gasoline at ratios of 15:1 or greater; alcohol at ratios up to 5:1.

#### PART NUMBERS

KL-200	10 QT CASE
KL-205	4 GAL CASE
KL-200 30 GL	30 GAL DRUM
KL-200 55 GL	55 GAL DRUM

#### RECOMMENDED APPLICATIONS

R/C Modeling:  
2/4-stroke glow  
Motorcycle/ATV:  
2-stroke alcohol, Stock,  
Hi-performance  
Kart/Micro Sprint:  
2-stroke alcohol, Stock,  
Hi-performance,  
4-stroke alcohol, Stock,  
Hi-performance, Road Racing

Klotz Synthetic Lubricants  
Fort Wayne, IN USA

Order Online: at [klotzlube.com](http://klotzlube.com)  
Tech Line: 260.490.0489

Order Line: 800.242.0489  
Email: [salesteam@klotzlube.com](mailto:salesteam@klotzlube.com)

©2018 Klotz S.L., Inc Tech Sheet