



#70812 & #70815 - Rear Bumper for the Traxxas Electric Rustler

What's Included: 1 - Rear Bumper, 4 - Stepped Spacers, 4 - Straight Spacers & 4 - M3 x 20mm Buttonhead Screws.

Needed for Installation: The **RPM** Rear Bumper for the Traxxas electric Rustler does not include a bumper mount. You will need an **RPM #80902 - Black or RPM #80905 - Blue Bumper Mount**, a Traxxas #3677 Bumper Mount or a Traxxas #3678 Wheelie Bar that includes the bumper mount. Any of these options will work but for the best performance, we recommend the **RPM** version.

Installation (without a Wheelie Bar):

1) If you haven't already done so, install your **RPM** or Traxxas Bumper Mount per the instructions that came with your preferred mount before proceeding.

2) Find the four spacers that have a uniform diameter (no steps). Referring to the illustration to the left, orient the **RPM** Rear Bumper as shown and slip the spacers between the lower legs of the bumper and the bumper mount (**RPM #80902** shown here for reference - not included).

3) Refer to the illustration (below left). Bolt the assembly together using the 4 included M3 x 20mm buttonhead screws. Caution, do not over-tighten the screws.

Installation: (with a Traxxas #3678 Wheelie Bar):

1) If you haven't already done so, install your **RPM #80902** Bumper Mount now. If you intend to run the mount that came with your Traxxas wheelie bar, install it now, then remove the Wheelie Bar from the mount via the 4 shoulder screws (2 on each side). You may discard these screws since they will not be used for this bumper.

2) Refer to the illustration (above right). Slip each of the 4 included Stepped Spacers into the holes where the shoulder screws were that you removed in Step #1.

3) Refer to the illustration (below right). Align the mounting arms of your Wheelie Bar with the bumper mount, then align the **RPM** Rear Bumper as shown.

4) Bolt the assembly together using the 4 included M3 x 20mm buttonhead screws. Caution, do not over-tighten the screws.

